



An ISO 9001 & 14001 Certified Company



Technical Data Sheet

INDOFOAM CXZ

Foam Control Agent

INDOFOAM CXZ is an oil-soluble defoamer for all coating systems based on synthetic latex systems such as in paper coating, in synthetic latex emulsion for paints and adhesives.

INDOFOAM CXZ helps in reduction and prevention of foam formation and in effect gives considerable savings in production time and cost. It is extremely versatile defoamer with good compatibility in aqueous media.

A Blend of Hydrocarbons with non-ionic emulsifiers – APEO FREE

Physical Properties:

Appearance	: Hazy Pale yellow to whitish liquid
pH(1%) soln	: 7+/- 1.5
Solubility	: Soluble in Oil, Dispersible in latex paint
Defoaming Capacity	: Excellent
Sp. Gravity	: 0.89 ± 0.01

Advantages:

- 1) Controls foam generation in coating systems
- 2) Extends excellent brushability
- 3) Does not cause defect like fish eyes and provides good quality finished product
- 4) Retains efficiency even after storage.



An ISO 9001 & 14001 Certified Company

Technical Data Sheet

Recommended Dosage:

In general the rate of 0.2 - 0.5% of **Indofoam CXZ** calculated on the total quantity of paint system, will provide excellent results. The exact dosage will also depend upon the individual paint formulation. It is advisable to stir the material before use as it has common tendency of settling.

Shelf Life:

Indofoam CXZ can be stored for one year from date of manufacturing as it possesses good storage stability.