

Recommended Application Field

Application	Grade
Tile Adhesive	MK30M, MK40M, MK50M
Masonry Mortar	MK40M, MK50M
Crack Resistant Mortar	MK20M, MK30M, MK40M
Repair Mortar	MK10M, MK20M
Joint Filler	MK4000, MK8000
Interior Wall Putty / skim coat	MK40MS, MK50MS, MK70MS
Exterior Water Resistant Wall Putty	MK40M, MK50M, MK70M
Gypsum Plaster	MK40M, MK50M, B40
Self-leveling Compounds	MK400
Ceramic	ME4000, MF4000
Detergent	MK70MS
EIFS	MK60M, MK70M

Remarks: This table suits for general formulation system, to choose your optimal grades HPMC, we strongly suggest customers to consult technicians from Joinway.

Package and storage

Multilayer paper bag with inner P.E. film, 25 KGS net each.

It's recommended to use the product in rotation on a first- in first- out basis.

Storage under dry and clean condition in its original packaging and away from heat.

Health and safety

Please see separate Material Safety Data Sheet.

CAS Name: HPMC

CAS No.: 9004-65-3

HS Code: 3912.3900

JOINWAY PLANT

